



#### TECHNICAL SHEET

#### **ALUMINIZED 2-LAYERS COAT**

V2KAF

Aluminized aramid coat 450g/m<sup>2</sup>. Central Velcro and press-studs closure, externally covered with aluminized aramid fabric, mandarin collar. Inner side completely lined with flame retardant cotton 300 g/m<sup>2</sup>. All seams are Kevlar 50/3 sewn.

SIZE: M, L, XL, XXL, XXXL



BEST PROTECTION

## FROM HEAT:



**EN ISO 11611:2015**

**Protective clothing for welding and allied processes**

Little splashes of molten metal and radiant heat Class 2  
Resistance to surface flame A1  
Resistance to edge flame A2



**EN ISO 11612:2015**

**Protective clothing against heat and flame**

Limited flame spread	A1+A2
Convective heat	B1
Radiant heat	C3
Molten aluminum splashes	D3
Molten iron splashes	E3
Contact heat	F2

PPE CATEGORY: III

# V2KAF

## EU DECLARATION OF CONFORMITY:

Manufacturer, **IDEE COCCO ITALIA srl - Via Spinino 11/1 - 36050 Montorso Vicentino (VI)**

declares under his sole responsibility that the following personal protective equipment (PPE) is in conformity with the safety and health requirements of the EU Regulation 2016/425 Annex II and with harmonized standards listed below, and declares that it is identical to PPE object of the EU Type Examination Certificate (Module B) issued by the Notified Body RICOTEST Srl n°0498

Code and name of product	Description	Reference standard	Notified body	Certificate n°
V2KAF	Aluminized coat, lined	EN ISO 11611:2015 EN ISO 11612:2015	0498	166211701/OI

The present PPE is subject to the conformity to type based on internal production control plus supervised product checks at random intervals (Module C2) under the supervision of the Notified Body RICOTEST Srl n°0498.

Montorso Vicentino, 11.05.2021

The legal representative  
Valentino Cocco